Husqvarna TS 60 Tile Saw.





Cart lock keeps cart in place while moving saw.



Applications.

■ Cuts tile and brick up to 20" diagonal or 24" rip cuts.

Benefits.

- Innovative, patented Jet Stream Containment System keeps water inside the water pan.
- New rolling wheel system with Duracon wheels.
- Weighs 79 lbs. easy to carry.
- Able to make plunge and miter cuts.
- Extra long 26" cart for better tile support.
- Equipped with ElgardTM which indicates, via the LED, when the machine is overloaded to prevent motor damage and increases motor life.
- Electronic SoftstartTM helps starting with normal, slow-acting fuses and increases brush and motor life.
- Integrated wheels in frame allow saw to be pulled independently like a roller bag.
- Water flow system designed to keep pump protected from
- Larger blade flanges provide more support for blade core.
- Includes removable cart extension and height adjustable stand.
- See video at www.husqvarnacp.com

Cutting capacities.

24" (610mm)









Easy, smooth movement of TS 60 blade guard for fast plunge cutting of tile.

Product specifications.

	TS 60
Item no.	966610701
List price	\$1,175.00

Technical specifications.

-	
Blade diameter, in (mm)	10 (254)
Depth of cut, in (mm)	2-3/4 (70)
Bladeshaft, rpm	3,175
Power source	Electric
Power, hp	1-1/2
Engine manufacturer	Husqvarna
Arbor size, in (mm)	5/8 (16)
Rip cut, in (mm)	24 (600)
Diagonal cut, in (mm)	20 (508)
Cutting arm	Cast aluminum
Cutting table	Cast aluminum, rubber top
Voltage,V	115
Cycle	60
Phase	1
Full load amps	14.4
Starting amps	18
Weight uncrated, lbs (kg)	79 (36)
Weight crated, lbs (kg)	109 (49)
Dimensions uncrated, in (mm) LxWxH	39-1/8 × 25 × 21-3/4 (994 × 635 × 552)

Accessories.

		P
A Foot switch	169543	\$99.00
B Conditioning sticks - 60 grit	66040	10.00





Foot switch.

Conditioning stick.

Spare parts.

Drain plug	543046051	\$.6
Water pan	510225414	49.0
Water pump, 110V	525825601	20.0
Cart extension	522468404	20.0
Rip guide	522469501	15.0
Wrench	510225437	.9





16" x 26" conveyor cart better supports larger tile.



Dual-position miter cut capability, adjustable in seconds.

